



"We are not makers of history. We are made by history."

Martin Luther King Jr.

Contents

The World of Cultural Heritage

Cultural Heritage Collection Types and A Archives and Manuscripts Rare Books Archiving Transparent Film and Glass Plate Negativ Fine Art Reproduction Special Digitization Projects Multi-Spectral Imaging

Instant Capture vs. Scanning

Phase One Film Scanning Solutions
Phase One Film Capture Stage

Phase One Flat Copy Scanning Solution

Phase One Book Scanning Solutions DT Atom DT Versa DT BC100

Capture One for Cultural Heritage

Phase One iXH & iXG Camera Systems

Phase One XF Camera System

IQ Digital Back Range

Phase One Lenses Schneider Kreuznach Blue Ring lenses

Phase One AutoColumn Copy Stands Phase One RPS 2300XL – Floor stand Phase One RPS 1600 – Table top

Phase One 2-Motion Copy Stand

Cultural Heritage Solution Partners Phase One Digital Transitions, USA Cambo, The Netherlands Kaiser Fototechnik, Germany

Phase One Scanning Solutions

References

	4
Applications	5
	6
	7
Ves	8
	9
	10
	12
	16
	18
IS	20
	22
	22
	24
	26
	28
	34
	38
	42
	44
	44
	46
	46
	46
	48
	50
	50
	50
	50
	50
	52
	54



The World of Cultural Heritage

The Cultural Heritage world is diverse, with many different needs and challenges. For this reason Phase One offers modular and configurable solutions, which can be tailored to specific needs.

The need for digitization is rapidly growing, with increasing focus on public access, research and preservation of information for the future. Many museums and libraries with valuable collections are expanding their digitization efforts, with exciting possibilities, made available by the rapid growth of internet-access for everyone.

The history of Cultural Heritage photography is as longstanding as photography itself. Historic collections in museums and libraries have often had a dedicated photographic studio for creating photographs of sensitive material, or for producing paper copies for researchers and scholars, protecting the original objects from wear or even damage.

Changing from analog based film processing to digitally based media has introduced a completely new range of applications, and the possibility to share the material with Melk Abbey Library, Melk, Austria © Will Pryce

a much broader audience, while significantly increasing the reproduction quality. Preserving the past for the future is often a race against time, as much of the material has a limited lifespan before it is gone forever, thus solutions that enable rapid capture are not only necessary but often crucial.

Cultural Heritage Collection Types and Applications

All Cultural Heritage collections are unique and diverse, but due to the nature of collections, they often fall into distinct categories. In order to address the diverse nature of collections, Phase One invests in developing, implementing and delivering specialized and tailored solutions, designed to produce the best output quality, while ensuring material safety and efficient workflow.

The main collection categories are:

- Archives and Manuscripts
- Rare Books Archiving
- Transparent Material and Film Scanning
- Fine Art Reproduction



Image courtesy of the Royal Danish Library. Multi-spectral capture of note sheet by Danish composer Niels W. Gade.

Archives and Manuscripts

Documents, drawings, maps, manuscripts, photos, newspapers, musical scores, letters, post cards, and other flat objects in all sizes and shapes.

This type of work often requires a "set and forget" workflow where the camera and software are set up so that large numbers of flat objects can be recorded quickly while maintaining high resolution and accurate consistent color and luminosity.

The high resolution of the Phase One Digital Backs allows capturing several smaller objects at the same time, thus increasing speed and efficiency.

The requirement for lighting may be divided into two categories:

- 1. Uniform light over the entire surface, with strict requirements to color precision. This is often achieved by photographing the material together with a color chart, as a reference for recreating the correct and exact same colors in the future.
- 2. Directional light may be used to enhance texture and three-dimensionality of the object. This type of work often leaves artistic freedom to the photographer, as the choices of light will enhance certain features, while diminishing others, thus giving the image an interpreted look or style.

'John Rylands Library Hebrew Manuscript 6, Haggadah f.20 recto' Image reproduced courtesy of the Centre for Heritage Imaging and Collection Care © University of Manchester

Rare Books Archiving

A large part of the Cultural Heritage community works on Using a leveled glass plate with the camera set for fixed digitization of rare and delicate bound materials, such as books. focus on a copy stand will accelerate the capture process, and Digitization of books often requires special attention to the photographing both pages at the same time with one or two binding, that can be fragile, and will determine how the cameras will also increase productivity. material can be treated in the process. This fact can sometimes be the limiting factor when looking for fast capture turnaround.

Uniform lighting will typically be the choice of operation here, and will often be the same throughout when working with reflective material.





Transparent Film and Glass Plate Negatives

negatives, transparencies, including 35mm mounted slides, microfilm and all other transparent material.

Uniform illumination of the materials with good color reproduction is mandatory so that all color information may be retrieved during processing, sometimes involving inverting equipment substantially. Phase One camera based solutions the image from negative to positive.

The conversion process can be open to interpretation, as the base material for the original transparency varies. This is true especially for the earlier glass plates where the specific type of chemicals and processing used is unknown.

Vintage glass plate negatives, medium and large format Two rolls of film may behave very differently, both in the physical characteristics of the original base material and in their subsequent chemical development.

> Traditional scanner solutions work with fixed sizes, such as 24x36mm, 6x6" or 6x9", thus limiting the versatility of the work with all sizes of originals.

> There is a tremendous speed advantage in the instant medium format capture over scanning, which may speed up the process by a factor of 300 or more.

Fine Art Reproduction

3D and large flat objects such as sculptures, pottery, decorative arts and paintings, are often captured from a tripod in the photo studio or in the gallery and exhibition halls, ideally with uniform lighting to suit the object's character and the curator's requirement.

A whole range of different lighting can be used, from flash-based to continuous light to mixed light or even natural daylight. Best results are always obtained by using medium format camera solutions; either based on an SLR-type, or view cameras with tilt & shift movements.

The fastest workflow solutions comprise of a camera system such as the Phase One XF, available with the highest resolution sensors on the market.



Multispectral Imaging (MSI)

Multispectral imaging (MSI) captures light from a range of wavelengths - visible and invisible to the human eye - across the electromagnetic spectrum using special camera technology, light sources, and filters. The resulting "stacks" of images are used to analyze substances and surfaces to determine readability, authenticity, age, and material-characterization and distribution. Application areas include analysis of documents, polychrome surfaces, fabrics for purposes of conservation and research

into forensics and materials characterization. Phase One offers "Rainbow": a fully automated 100Mpixel multispectral imaging solution for both Multiband and Narrowband lighting techniques. Please refer to pages: 14-18.



credit "R.B. Toth Associates and Equipoise Imaging



Special Digitization Projects

Many cultural heritage objects that are fragile or sensitive due to various types of damage and decay are often very sensitive to human touch and thus require careful handling. Using high resolution, high precision cameras and optics allow researchers and scholars to perform non-invasive investigation and analysis with minimal or no exposure to aggressive light rays or chemicals, and bring out data that cannot be retrieved with traditional imaging techniques.

3D scanning combined with advanced photogrammetry and image analysis and calculation tools are used for measuring and evaluation of damage in historical objects. The same technology is used for creating exact replicas of precious sculptures and art work. The high resolution of Phase One cameras and the high quality and precision of the optics provide the basis for systems that are considerably faster than other scanning solutions.

Instant Capture vs Scanning

Speed

ASEON

Automation and Ease of Operation

Traditionally, flat objects such as documents and books have been scanned using flatbed or overhead scanners equipped with a linear CCD sensor. Some of these devices can produce high resolution, high quality output. However, scanning a single page can take up to 20-30 times longer than when using a singe-shot, high resolution medium format camera.

Image Quality

When capturing cultural heritage items, it is important to produce and maintain the highest image quality possible in terms of resolution, sharpness, tonality and color.

Phase One's high resolution sensors, Schneider-Kreuznach high precision optics, stable copy stands, and Capture One's advanced workflow and algorithms, enable the the collections' curators, photographers and to ensure that no detail gets missed and that their collections are archived to the highest level of quality for future use and preservation.

New high precision copy stands paired with the iXH or iXG camera systems and Capture One CH deliver "AutoColumn", automated camera column positioning achieving a wanted capture resolution.

Tools for auto-cropping and for automated conversion of film scans from negative to positive also add to the move towards automation. As does "Slipstream", the new Phase One simplified capturing UI.

Highest Resolution with ISO Compliance

The Phase One camera systems deliver scanning resolution of up to A0 @300ppi or A1 @400ppi or A2 @600ppi - all in compliance with the industry standards of Metamorfoze, FADGI and ISO 19264.

RAW Workflow

Unlike scanners, the RAW files coming from the Phase One cameras and digital backs contain the RAW data and all the relevant information necessary for processing and reprocessing. This ensures a future-proof workflow and a file that can be used time and again as needed and as software performance develops and improves.



115. Hivbs neuer Wohlfand. Hiob 42, 10-14.



Einheimischen unter den Kindern Ifrael; Breite zehn taufend Ruten haben. *2. Moje 22, 20.

23. und sollen auch ihren Teil am Lande haben, ein jeglicher unter dem Stamm, dabei er wohnet, spricht der Herr, HErr.

Das 48. Kapitel.

Berteilung des Landes. Umfang der heiligen Stadt und Namen ihrer Tore.

1. Dies find die namen der Stämme. mein Land sein zur Stadt, drinnen zu Von Mitternacht, an dem Wege nach wohnen, und zu Vorftädten; und die Stadt * Hethlon, gen Hamath und Hazar-Enon soll mitten drinnen stehen. und von Damaskus gegen Hamath; das 16. Und das foll ihr Maß sein: vier foll Dan für seinen Teil haben, von Mor= tausend und fünf hundert Ruten gegen gen bis gen Abend. Mitternacht und gegen Mittag, desgleichen * R. 47, 15. 17. 2. Neben Dan soll Affer seinen Teil gegen Morgen und gegen Abend auch vier haben, von Morgen bis gen Abend. taufend und fünf hundert. Dffenb. 21, 16. 3. Neben Affer foll Naphthali feinen 17. Die Vorstadt aber soll haben zwei Teil haben, von Morgen bis gen Abend. hundert und fünfzig Ruten gegen Mitter= 4. Neben Naphthali foll Manasse seinen nacht und gegen Mittag, desgleichen auch Teil haben, von Morgen bis gen Abend. gegen Morgen und gegen Abend zwei 5. Neben Manaffe foll Ephraim feinen hundert und fünfzig Ruten. Teil haben, von Morgen bis gen Abend. 18. Aber das übrige an der Länge neben 6. Neben Ephraim soll Ruben feinen dem Abgesonderten und Geheiligten, näm= Teil haben, von Morgen bis gen Abend. lich zehn taufend Ruten gegen Morgen und 7. Neben Ruben soll Juda feinen Teil zehn tausend gegen Abend, das gehöret zur gaben, von Morgen bis gen Abend. Unterhaltung derer, die in der Stadt arbeiten. 8. Neben Juda aber fallt ihr einen Toil 19 Und Macheiter aus allen Ette

Flexibility

Future-proof tethering: With the Infinity platform of IQ4, the tethering options of Ethernet, USB-C, and WiFi provide many possibilities for flexible installation and workflow.

Advanced storage: The IQ4 ensures security and speed with both XQD and SD local storage options.

Multi-purpose use: Unlike scanners, a camera mounted on a copy stand can be moved up/down and can use different lenses to accommodate different object sizes, and of course can be mounted on a tripod allowing complete portability and flexibility in photographing almost anything.

Upgradability

With the advancement in technology and improvements

in sensor resolution, optics, and software algorithms, each component of the camera system can be changed or upgraded to take advantage of these advances, while keeping the same basic setup and workflow.

Low Maintenance

Collections often include hundreds, thousands, or even millions of items that need to be digitized and reproduced consistently and accurately

The Phase One iXH 150MP and iXG 100MP Camera Systems are designed and tested to withstand the toughest working conditions. They are built with minimal number of moving parts and heavy duty leaf shutters, ensuring long life and low maintenance intervals. Modular design allows for quick and easy swapping of components when it is time for service, and the local support provided by a network of trained, value added resellers ensures continuous uptime and fast turnaround.



Phase One iXH 150MP 1edium Format Camera





der Kreuznach enses from 45 mm to and and ano districtly tutiletto tito bie

14. Und sollen nichts davon vertaufen, noch verändern, damit des Landes Erft= ling nicht wegkomme; denn es ift dem HErrn geheiligt.

15. Aber die übrigen fünf taufend Ruten in die Breite gegen die fünf und zwanzig taufend Ruten in die Länge, das foll ge=

Phase One RS 72mm MkII lens Schneider Kreuznach RS 72mm lens



Copy Stand solutions from Cambo, Kaiser, Digital ansitions and Phase One



CULTURAL HERITAGE

Phase One Flat Copy Scanning Solutions

A0@300ppi Scanning with AutoColumn

The Phase iXH 150MP and iXG 100MP systems give the
highest levels of resolution and flexibility allowing capture of
large objects such as drawings and maps, as well as smaller
objects such as books and manuscripts. Sensors with up to
150MP deliver scanning resolutions of up to A0 @300ppi, fit
for the most demanding digitization projects.AutoColumn is available with
the RPS 2300XL copy stand.
The RSP 2-Motion repro stand
the object to be moved and
object sizes and resolutions.
With the Schneider Kreuzna

Components

The General Purpose Kit includes

- Phase One iXH 150MP or iXG 100MP
- Phase One AutoColumn RPS 2300XL copy stand or Phase One RSP 2-Motion motorized copy stand
- Capture One CH

Features and benefits

- Solid, reliable and durable build
- Easy, fool proof operation
- Maximum adjustability
- 2-speed, self-limiting worm gear for

AutoColumn is available with iXH 150MP and iXG 100MP and the RPS 2300XL copy stand.

The RSP 2-Motion repro stand allows both the camera and the object to be moved and thus capture a wide range of object sizes and resolutions

With the Schneider Kreuznach lenses, both sharpness and detail are maintained across the field of view.

• Up to 400 times faster than traditional scanners

• Consistent, reliable Autofocus with excellent manual

accurate positioning

• Max. camera load of up to 15 kg

• Flexible and modular design

Live View adjustment

0

Phase One iXH 150MP / iXG 100MP Medium Format Camera System



Schneider Kreuznach RS 72 Mk II Schneider Kreuznach LS 80 mm f/2.8 lens

Phase One RPS 2300XL AutoColumn copy stand

Phase One RSP 2-Motion motorized copy stand



Capture One Cultural Heritage

z-speed, sen-inning won



Phase One **Film Scanning** Solutions

Scanning Transparent Film and Glass Plate Negatives

With a capture rate of one image per second, the Phase One Film Scanning Solutions are up to 400 times faster than flatbed, drum or virtual-drum scanners.

Regardless of the density or size of the original glass or film negative or transparency, it provides a consistent and reliable workflow, ensuring that that the highest levels of image quality and accuracy are met.

The newly designed Phase One Film Capture Stage provides an adjustable, geared support mechanism and is compatible with a range of carriers for glass plate negatives as well as most popular film strip and sheet formats. It can be easily adjusted to position the object directly under the camera. Made of high-grade aluminum, it ensures longevity and reliability for many years.

The film carriers, also made from aluminum, are designed to maintain film flatness with a minimal amount of stress and easy mounting/dismounting.

The glass plate carriers support most common and odd plate formats and are equipped with an optically optimized glass base. These too are made of high-grade aluminum and are built to last. They provide an economical solution for almost all types and sizes of plates.

With sensitive glass and film transparencies and negatives, material handling and its safety are key and the Phase One Film Capture Stage offers the ideal solution for a wide range of applications.

The Phase One iXH 150MP and iXG 100MP Camera Systems come with a Schneider Kreuznach 120mm Macro RS lens



equipped with the Reliance Shutter, rated at 1 million actuations and allowing for reliable and consistent capture of the finest detail with minimum amount of vibration.

The Phase One XF Camera System comes with a Schneider Kreuznach LS 120mm f/4.0 Macro lens designed to produce a flat image and thus ensuring maximum sharpness across the frame.

Check out the full Phase One portfolio of scanning solutions for Cultural Heritage at the end of this guide.





Phase One Film Capture Stage

Specifications

Dimensions (WxHxD)

Weight

Phase One Film Carriers and Glass Plate Holders

Made of milled high-grade aluminum and using optically optimized glass base, they maintain parallelism and flatness.

The Film Carriers work with specially designed clamps that carefully stretch and flatten the film strips.

Supported film formats:

- 120 mm strips
- 9 x 12 cm
- 13 x 18 cm
- 18 x 24 cm
- 4 x 5 in.
- 8 x 10 in.

- 9 x 12 cm
- 13 x 18 cm
- 18 x 24 cm
- 24 x 30 cm

The newly designed Film Capture Stage provides an adjustable, geared support mechanism and is compatible with a range of carriers for glass plate negatives as well as most popular film strip and sheet formats. It can be easily adjusted to position the object directly under the camera.

730 x 216 x 700 mm (28.7 x 8.5 x 27.5 in.) approx. 13.5 kg (29.7 lbs)

The Phase One Film and Glass Plate Carriers are designed to work with the Film Capture Stage, ensuring smooth handling and efficient workflow.

- 35 mm strips
- Mounted 35 mm slides

The Glass Plate Holders work with specially designed "top stop" which ensures accurate and quick positioning of glass plates of the same size.

Supported glass plate formats:

Phase One **Book Scanning** Solutions

Digital Transitions DT Atom Flexible Scanner with Book Digitisation Cradle

The DT Atom is a tabletop digitization platform, featuring AutoColumn, that can be extended and upgraded to accommodate nearly any digitization project. The user can unlock the Standard Hardtop and swap to a variety of accessories to better accommodate different material types. The camera can be removed and used on a tripod or handheld. In this way, it can be used for architectural, portrait, installation art, and other photography.

DT V Cradle

Compatible with the DT Atom, and DT Versa and all legacy Digital Transitions work stations, the DT V Cradle provides conservationfriendly, preservation-grade, fast and efficient digitization of A3 bound material (up to 17" x 12"). Its unique design incorporates a tilt-inward mount for the camera to provide ergonomic digitization without increasing the footprint of the system.

The optional glass uses a lift-assist mechanism to improve the ergonomics of the user over long periods of use. The glass can be fully removed in less than a minute when even the minimal operatorcontrolled contact with the glass is not suitable for a given material. To ensure the safety of the binding, the mechanism of the book platform freely slides forward and backward to guarantee the gutter is always properly aligned to the captured frame. This also ensures the glass, if used, cannot produce undue pressure on the binding.

DT Atom with DT V Cradle, Features & Benefits:

- AutoColumn functionality when used withiXH 150MP andiXH 150MP and iXG 100MP 100MP and Capture One CH.
- Easy to operate and works as mobile solution
- User-swappable tops for wide range of materials
- Operated by foot and/or hand releases
- Includes DT Photon LED lighting (CRI/CQS of 98)
- Allows book opening of 80°, 100°, or 180° •
- Allows capture with or without glass
- Glass lift-assist for long-term use ergonomics
- Open platform design allows upgrading resolution, thereby preventing obsolescence.



Digital Transitions DT Versa All-purpose Digitization Cradle



Originally designed and built for the National Archives Records image capture and can also leave documents partially open Administration, the DT Versa Reprographic Capture Cradle when the binding is too fragile and cannot be completely is the latest integration of book capture and reprographic flattened. technology.

camera systems to achieve preservation grade reproductions at the fastest rate of capture - while providing reliability, ease table and includes lift-assist gas pistons and is secured with of use, and safety of the original materials - the DT Versa is hand locks. the optimum digitization solution for the rapid capture of rare, bound and loose document collections.

The DT Versa features a built-in pneumatic 180° dual platen technologies or needs change. book cradle that adjusts to the thickness of bound collections. The system is designed to bring printed materials to optimal To increase versatility, a 76.2 x 101.6 cm copyboard is also to 10.2 cm bindings.

The DT Versa is operated by foot pedals and can be fine-Developed with AutoColumn for the iXH 150MP and iXG 100MP tuned to protect the widest range of materials. For increased safety, the glass top is hinge-mounted to the back of the

> The DT Versa features a modular design that incorporates today's finest digital camera systems and can be upgraded as

focus and accommodates books up to 63.5 x 89.0 cm with up included that can be placed over the glass so that oversized books, foldouts, maps, rare materials, paintings, film and glass negatives (utilizing the Phase One Film Capture Stage), and The book cradle platens are self-adjusting platforms that more can be digitized. The DT Versa Capture Cradle is truly utilize dual pneumatic pistons for raising and lowering. The a proficient system that will protect your investment and platforms gently push the books against the glass plate for enable you to expand the scope of your digitization program.

Digital Transitions DT BC100 Dual Camera Book Cradle Solution

Built on the success of the DT Reprographic System, this system redefines the way library materials are digitized. The BC100 is the only true 48 bit system on the market that will meet the high demands of cultural institutions by providing the highest image quality, speed, and reliability needed to capture a wide variety of bound and loose materials - all while protecting the original documents.

Designed for the mass digitization of books, the 100° the tendency to skip or damage fragile pages and the need for bonded v-shaped anti-reflective glass platen and adjustable manual assistance book cradle secures and holds the largest variety of bound The BC100 has also been constructed with the comfort of the materials with page sizes up to 17"x24" or A2 size per side.

operator in mind. The operator sits in the station and controls the system with a variety of foot and/or hand releases, These combined components keep the focus plane the same thereby preventing repetitive stress injury. All operations are while being gentle on the binding of the book. The glass within arm's length and the lights are at a pleasant level. There platen of the DT BC100 is designed with a pneumatic lift are extra shelves allowing the operator to have computer system to increase productivity while protecting the books, displays and other equipment nearby. and is incapable of free falling.

To ensure the safety of the binding, the mechanism of the book platform slides back and forth and then sets to make certain that the glass platen is always in the middle of the book's gutter. The platform rests on a controllable support system that may be adjusted by the operator for different book types. This system has been designed to address the shortcomings of of your mass digitization projects. traditional robotic systems, including lack of quality control,



The modular design of the DT BC100 allows the camera and capture device to be upgraded when necessary, ensuring that it will not become obsolete. It is fabricated with airplane grade extruded aluminum to .005" tolerances, so it will not break down after years of continuous use. The versatile features and reliability of the DT BC100 make it the ideal solution for all

Features & Benefits:

- Dual Camera Book Capture System with an incredible rate of capture.
- Capable of shooting bound and loose materials, including works on paper, serials including newspapers, loose manuscripts, photos, drawings, etc.
- 100° anti-reflective glass platen enables the digitization of up to 6" bindings and page sizes up to 17" x 24" or A2 size per side.
- Delivers preservation grade TIFFs, JPEGs, and PDF's in RGB, grayscale, and CMYK modes. Open Source Raw and DNG also supported.
- The only true 48 bit system on the market.
- Operated by foot and/or hand releases.
- Four retractable vibration dampening casters.
- Open platform design allows camera and capture devices to be upgraded, thereby preventing obsolesence.
- Variable resolution options available.
- Compatible with our DT Reprographic Systems for increased versatility.
- Easy to operate.
- Durable design for years of continuous use.

Capture One for Cultural Heritage Solutions





CULTURAL HERITAGE

The new Slipstream mode - a simplified user interface enables less-skilled operators to handle the capturing, and it speeds up the workflow, especially when working on large collections and large volumes of documents that need digitization.

production.

and much more.

Negative Film Reproduction Tool and Styles

Take advantage of the improved workflow, automating the conversion of negative transparent material in both black & white and colors. Use the intuitive exposure tools to adjust exposure, contrast and colors, and get perfect results for print or further post-processing.

A selection of Cultural Heritage styles allows to quickly choose a set of conversion parameters for different film types.

Capture One CH is a professional Rapid Capture Solution dedicated to the Cultural Heritage community. Built on the renowned Capture One software, the Cultural Heritage edition offers a highly specialized featureset that delivers a significantly faster reprographic workflow during both capture and post-production.

The ever-evolving Capture One CH offers key features designed to increase productivity and efficiency when working with high-volume collections. With extra specialist tools and automation technology, the software expands on the admin and operator toolboxes to facilitate modern production needs and prevent bottlenecks commonly created in large-volume

A Quantum Leap in Productivity

Use Capture One CH to optimize your images. Not only do you get the highest image quality from the advanced image-rendering engine, you also have access to powerful adjustment tools to fine-tune your images for final presentation, digital asset management, for archival and retrieval,

Auto Crop & Auto Rotate

Boost productivity by automating cropping in postprocessing. Select cropping options for flat art reproduction or books, including corner or edge alignment with positive or negative padding for all cropping methods.

Save time with On-Capture multi-crop when digitizing books that do not require the full resolution of the camera, where 2 pages can be captured and separated on the fly. Use an advanced auto-cropping setup for film rolls and strips that includes straightening and post-crop auto levels optimization.

		* Default conventions	
300000000000000	(2) % B. D.	9.3.11.01.11.1	
HETCOMM			BABAZIGOS
		an is re T	THE REPORT OF TH
			A COLUMN A
0 M 10 M 10		100	
000			
Real Designation			
The Art + 1974			
Com Charles Town			THE CONTRACTOR OF A
approximate and a second secon			and the second se
		Cire -	
			245
Among Co. 1998			500 C
Annual CO Man			9-9-
n = # 1			And a second s
NOWNOW & PLP	Matura Beating	and the second se	Contraction of the local division of the loc
Augu (1)	Smighter Away		
· · · ·	Public 40 pt	end at 17 De monostrativi	And Address of Concession, Name
No New C	Co-Color		
		And the local data and the local	
V CAPTURE RESOLUTION RALER			
Brow Ruler Ch Image			and the second se
Longit 120 In			and the second
Resolution and per-			P
		100	
			Company of the second se
			1 PARCELED A
			and the second second
		No. of Concession, Name	
		and at 10 percent at 10 percent	
	8010 VMI +		

Camera Focus with Auto Column and PPI-Assist

In combination with theiXH 150MP and iXH 150MP and iXG 100MP 100MP camera, the Camera focus tool delivers accurate measuring of distance to object and based on that it calculates the capture resolution, magnification and Field-of-view. The data is calculated for current camera position and delivers precise data for automated or guided re-positioning the camera to capture at target ppi, magnification or Field-of-view. Check out the AutoColumn solutions available at the end of this guide.



Capture Resolution Ruler

The Resolution Ruler delivers verification of the capture resolution at any given camera position. It allows for marking up a known length in the target subject matter, in inches or centimeters, and calculating the exact capture resolution.

Slipstream Capturing for non-trained Operators

Slipstream delivers a simplified, easy to use capturing interface allowing non-skilled operators to handle the capturing process. Slipstream works on top of the Capture One CH platform. This facilitates interfacing and access to the admin tools for camera setup, for post processing, and for image storage matching the needs of both simple and advanced networking environments.





Barcode scanner tool

The integrated Barcode Scanner tool ensures that objects are named and identified correctly as they are captured. Use it together with the Next Capture Naming tool.



CH Workspaces

A Capture One CH workspace is a logical setup with a Collection of tools customized to optimize a given CH workflow. Workspaces may be made for tailoring the user-interface for preparation, for production and for file storage. It can include the required capture and processing tools for specific Reflective or Transmissive materials. Workspaces can be used by both admin and Operator personnel.

Tools Lock

Admins can lock specific tools (individually or as a set) so that they cannot be accidentally altered by operators during capture. Assign pin codes to specific tools to prevent operators from changing important capture properties or settings.

ICC Profiles for Cultural Heritage

Obtain high color accuracy with the specialized ICC profiles optimized to be robust under the slight changes happening to lighting over time. The profiles work for both flat art and three dimensional objects. Available for common studio light types such as flash, LED and tungsten as well as for specific types of film.

Creative Enhancements

Advanced Color Editor can help to achieve monochrome images or to enhance selected colors. In order to achieve the perfect image, Capture One CH offers an Enhanced Color Editor and also a black & white Tool. Capture One CH offers a vastly improved noise reduction, especially for higher ISO images.

Phase One **Rainbow** Solution





Non-invasive & nondesctructive contactless analysis



Quick first step for further analysis -Do it once, do it right



Nondestructive thanks to low energy LED lighting



Modular & mobile capturing solutions

Discovering Multispectral Imaging (MSI)

Multispectral imaging (MSI) captures light from a range of wavelengths - visible and invisible to the human eye - across the electromagnetic spectrum using special camera technology, light sources, and filters.

The resulting "stacks" of images are used to analyze substances and surfaces to determine readability, authenticity, age, and materialcharacterization and distribution.

MSI in a wide range of applications

- 1. Analysis of documents Readability of text on parchment, scrolls, and paper, often in poor condition is one application.
- 2. Analysis of polychrome surfaces such as paintings on canvas, wood, stone, and other materials. Applications include noninvasive analysis for conservation work and authentication.
- 3. Analysis of Fabrics of all kinds -such as historic research to determine age and material.
- 4. Police, forensic and crime scene investigation. Analysis for of weapons, and crime scene evidence.
- 5. Materials characterization and sorting. Applications include and analysis for machine vision.
- 6. General: MSI is used to differentiate subject matter based chemical compositions



Images credits R.B. Toth Associates / Equipoise

residue of human fluids on fabric, fingerprints, marks from use

quality assurance, research and development of new materials,

upon the differentiated response from materials with different



Imaging

The Rainbow Multispectral



Credits Loa Ludvigsen (SMK) & Annette T. Keller (Phase One)

The Rainbow Software

Multispectral cameras have been available in the market for many years but the calibration process, as well as the techniques for changing material sizes whilst maintaining consistent images that can be stacked and analyzed efficiently, has been a challenge and created significant overhead.

Phase One has worked with specialists on MSI projects over years. Based upon this experience and learning, we have devised a flexible and easy to handle, yet robust MSI solution with a workflow based on best practices.

The Rainbow capture process is fully automated: simply position the subject matter and press 'Capture'. The full stack of captures are then made with automated focus, automated "flattening", automated exposure normalization, and automated alignment to deliver the Perfect Stack, again and again - with perfect repeatability and stability.

The Rainbow MSI software controls all the elements - Focusing the camera, moving the filter carousel on the filter wheel, turning the lights on and off in the correct order and timing, aligning the images, and finally creating the Perfect Stack.

The Rainbow Camera

The iXG camera is presented on pages 34-35

The Rainbow LED Lights

Rainbow supports two types of LED lights for a wide range of applications:

• Multiband DedoLight, delivering narrowband UV, broadband visible light, broadband and narrowband IR. This light is often used for MSI applications related to Art Conservation and to

Police Forensics. Recipes for the capture of images following the CHARISMA standard manual are included.

• Narrowband EurekaLight, delivers 16 narrowbands of light from UV, through visible to IR. Narrowband MSI is used for a range of research disciplines, including the analysis of inks, paints, residues, and features in manuscripts, objects and artwork

The Rainbow Filter Wheel

The filter wheel can hold up to five filters. It is configured to support the filtering needs of accurate visible imaging and luminescence imaging, which fits many applications, including the CHARISMA standard manual.

The carousel, which holds the filters is removable and can be configured with any 2" filters for future scientific applications. The factory capture settings can be adjusted to suit different filter configurations. To support different MSI applications, you can simply work with two or more filter carousels.

Phase One Expert Team

The Rainbow MSI solution can be tailored for a wide range of applications. The Phase One Expert team is ready with customer guidance to configure the best solution for a given application. Advice is backed up with online demonstrations and sample imaging from the Phase One MSI demo center in Cologne, Germany.

For feasibility studies, smaller projects, and operational support, Phase One offers workshops in which specialists can take the customer through the basics of MSI, and the capturing of relevant samples, directed at the MSI projects in question.

Multispectral Imaging in Use

1. The National Gallery of Denmark

The National Gallery of Denmark owns a painting acquired hundreds of years ago through the Danish Royal Family. The painting has been inspected and analyzed several times to determine its origin and creator, without success. In the fall of 2019, the painting was analyzed again by using wide spectrum photography at a high resolution with a sequence of different lighting, including UV light, visible light in reflectance and photo-induced luminescence, and IR light. The IR image disclosed the painted signature "BRUEGHEL 1562" in the upper right corner. Authentication of a Pieter Bruegel the older masterpiece was well under way.

Credits Loa Ludvigsen (SMK) & Annette T. Keller (Phase One)



2. The Royal Library of Denmark

The Royal Library of Denmark holds collections of handwritten letters and records from the former Danish colonies in Tranquebar, India (1620-1845) and St. Croix, the West Indies (1672-1917). Many of these documents are faded and decayed by age, by moisture and from bugs. In 2017 samples from the collections were captured using Multispectral Imaging and the results included the recovery of readability and the appearance of watermarks in the paper.



Copyrights Royal Danish Library - August 2015 & Equipoise Imaging/RB Toth Associates

3. Police and Forensics

Many disciplines of MSI analysis are applied within Police work. Here is an example of gunshot residue - discovered by photoinduced IR luminescence.



Copyright Annette T. Keller Phase One

The Rainbow MSI Solution

	IXG IOUMI	P wide Spectrum		
Sensor size	53.4 x 40.0			
Resolution	11608 x 8708			
Pixel size (μm)		4.6μm		
ISO Range	5	0 - 6400		
Data Interface		USB3		
File Formats	Raw 14	Raw 14bit, Raw 16bit		
Lenses	Schneider Kreuznach RS 72mm and/ or 120mm			
Weight (gr) with 72mm lens	2,300 inc. L - Bracket			
Dimension (mm) with 72mm lens	150 x 130 x 130 inc. L - Bracket			
Approvals	FCC Class A, CE, RoHS			
Operating Temperature (°C)	-10 to 40			
Operating Humidity (%)	15 - 80 (non-condensing)			
Accessories	BG39 filter for normal photography, with magnetic adaptors. Custom lens shade suited for the supplied filter wheel			
	Multiband Solution	Narrowband Solution		
Included LED lights	2 x UV, inc. UG11 filters (365 μm) 2 x VIS, inc. BG39 filters 2 x IR (860μm & 960μm)	Wavelengths (μm): 365, 385, 410, 420, 450, 480, 510, 530, 550, 600, 630, 640, 660, 740, 850, 940		
Configuration	2 banks with UV-, VIS-, IR- emission each	2 panels with 16 LEDs in each		
Filter Wheel (5- position)	Included, controlled via USB			
Communication with lights and filter wheel	USB via 7 - port powered hub			
Light stands	Not included			

	IXG IUUMP Wide Spectrum		
Sensor size	53.4 x 40.0		
Resolution	11608 x 8708		
Pixel size (μm)		4.6µm	
ISO Range	50) - 6400	
Data Interface		USB3	
File Formats	Raw 14	oit, Raw 16bit	
Lenses	Schneider Kreuznach	n RS 72mm and/ or 120mm	
Weight (gr) with 72mm lens	2,300 inc. L - Bracket		
Dimension (mm) with 72mm lens	150 x 130 x 130 inc. L - Bracket		
Approvals	FCC Class A, CE, RoHS		
Operating Temperature (°C)	-10 to 40		
Operating Humidity (%)	15 - 80 (non-condensing)		
Accessories	BG39 filter for normal photography, with magnetic adaptors. Custom lens shade suited for the supplied filter wheel		
	Multiband Solution	Narrowband Solution	
Included LED lights	2 x UV, inc. UG11 filters (365 μm) 2 x VIS, inc. BG39 filters 2 x IR (860μm & 960μm)	Wavelengths (µm): 365, 385, 410, 420, 450, 480, 510, 530, 550, 600, 630, 640, 660, 740, 850, 940	
Configuration	2 banks with UV-, VIS-, IR- emission each	nks with UV-, VIS-, IR- emission each 2 panels with 16 LEDs in each	
Filter Wheel (5- position)	Included, controlled via USB		
Communication with lights and filter wheel	USB via 7 - port powered hub		
Light stands	Not included		
Included Capture Computer	DELL Mobile Precision 7740 CTO BASE, 17.3", i9 processor, 64GB RAM, 1TB SSD, Windows 10 OS		
Workflow Software	Phase One Rainbow MSI software		
Output	8-image stack, according to Charisma Guidelines 16-image monochrome stack, ready for statistical analysis		
Output Luminescence	3 channels 15 channels		



specification

Camera

System specification



1. iXG 100MP Wide Spectrum camera incl. magnetic IR/UV cut filter & hood 2. MSI accessory kit incl. Filter wheel, mounting rail, USB hub, PC and software 3. Multiband/ Charisma Dedolights, including filters, power supplies and USB power switches* 4. Narrowband Eureka Lights* 5. Copystand (desktop/ floor/ wall)*

*Light stand and copystand not included

Phase One iXH & iXG Camera Systems





Cultural institutions have the staggering task of achieving Phase One'spatented imaging capabilities. The efforts have perfection in the preservation of their collections. Phase One delivers to the need for intelligent capture solutions built to designed with quality, durability and ease of use in mind, a process high volume digitization programs with speed and wide range of applications, and they come with a complete accuracy. Our specialized research and development team software integration into Capture One CH. These cameras have developed a configurable solution that provides an accurately measure distance to object matter and record the

yielded the **iXH 150MP** and **iXG 100MP** Camera Systems; both ergonomic and efficient workflow, resilient hardware, and resolution (PPI), Field-of-view and magnification, making it

easy to position them on any copy stand for a given scanning types of film and glass plates can be readily digitized. purpose. We refer to this functionality as **PPI-Assist.** In The configuration of the iXH 150MP and iXG 100MP solutions combination with the Phase One AutoColumn copy stands go hand-in-hand with the development of Capture One and Capture One CH, the iXH 150MP and iXG 100MP Cameras Cultural Heritage software. Our iXH 150MP and iXG 100MP are integral for delivering automated camera positioning for a Camera Solutions are designed with quality, material safety specified PPI. With the Phase One Film Capture Stage, all and an efficient workflow in mind.

IXH 150MP & IXG 100MP

Camera Systems

Technical Specifications

A0 @300ppi

The **iXH 150MP** is Phase One's first camera system purposely built for reproduction and that is capable of capturing a singleshot, AO size at 300ppi while meeting the stringent imaging required for specialized scientific imaging applications, standards such as Metamorfoze, FADGI and ISO 19264.

USB-C and 10G Ethernet data interfaces on the iXH 150MP deliver the highest transfer rates and flexibility to suit different are the tool of choice for imaging applications such as needs and workflows.

Best Flat Field Repro Optics New Phase One RS 72mm MkII lens

Designed from the ground up, the new Phase One RS 72mm MkII lens delivers top performance and optimization for the iXH 150MP. Its floating element increases precision at all apertures and magnification ranges, from 1:70 to 1:3. The iXH 150MP Camera is also available with the Schneider Kreuznach 120mm lens. The two lenses allow flat copy work to meet the demands of libraries, archives, and universities. The lenses keep the color uniformity required for the most demanding reproduction applications. The **21mm** and **42mm** extension tube accessories, used with the **120mm** lens, are designed with the same accuracy and quality as the camera body and lenses, allowing close-ups at a higher resolution, resulting in accurate capture of small objects.

The iXG 100MPs utilize integrated flat field optics with the Schneider Kreuznach 72mm and 120mm lenses, addressing the needs of flat copy work, being particularly useful for libraries, archives, and universities. In combination with the digital lens profiles of Capture One CH, the lenses offer the highest quality in terms of resolution, flatness, sharpness, lack of distortion and color uniformity required for the most demanding reproduction applications. 21mm and 42mm Extension tubes are available for close up capturing of film and small objects at higher resolution and are designed and built with the same accuracy and quality as the camera body and lenses.

Color accuracy & superior detail

The **iXH 150MP** and **iXG 100MP** Camera Systems use CMOS sensors (the 150MP is also **Back Side Illuminated**) with an outstanding dynamic range of 15 f-stops to ensure the highest multi-spectral and 3D applications. resolution, sensitivity and lowest level of noise. They produce the most accurate colors and details thanks to advanced electronics and processors that allow for high accuracy in the reproduction of Cultural Heritage applications such as artworks and precious books

The Achromatic and WS (Wide Spectrum) models combine the highest resolution and class-leading spectral sensitivity research and conservation of manuscripts, maps and drawings. With its ability to capture in color, UV and IR, the WS cameras paintings, medical and forensics. By simply adding an IR block filter, they convert to a regular camera. The **iXG 100MP WS** is also one of the key components of the Phase One Rainbow MSI solutions (see page 30).

AutoColumn and PPI-Assist

The full integration of hardware with the customized Capture One CH software yields an efficient, professional workfow and precision results. In Addition, the Phase One AutoColumn copy stands, Capture One CH, and iXH 150MP Camera System deliver automated camera positioning for a specified ppi.

Industrial durability: one million actuations guaranteed

The iXH 150MP and iXG 100MP offer industrial build-quality, made with aerial-grade aluminum and the most durable mechanical and electronic components available today. The camera's mechanical Reliance Shutter is offered with one million actuations guaranteed. In electronic shutter mode, an unlimited number of shutter actuations can be achieved. The newly designed housing with its integrated heat sink and cooling fins, ensures that the temperature remains low even during long days of running Live View continuously, and thus producing noise-free images and consistent results.

Scientific Tools and SDK for integration

The iXH 150MP and iXG 100MP Camera Systems and the Phase One SDK are designed to provide an open platform for new imaging applications. For example, with the addition of accessory lighting and filtering, the wide spectrum, infrared, and multi-spectral capabilities of the iXH 150MP and iXG 100MP meet the highest standards required. The capabilities and incredible focusing accuracy, open the door

to computational and sequential imaging, required for both

System specification

iXH 150MP, iXH 150MP Achromatic and iXH 150MP Wide Sprectrum - all with BSI sensors	
Relian C	
٦	
VHQ L-Bracket with st	
USB-c/ 10G Ethernet	
Flash Output, LED light control, remote triggering	
Integrated cooling fins and heat sink	
227 x 130 x 130 inc. L-Bracket with 72 mm MkII lens	
3,450 inc. L-Bracket with 72 mm MkII lens	
Phase One 72mm Mkll	

Magnification range	1:70 - 1:3 (optimal 1:11)
Lens thread	

Lens thread	77
diameter (mm)	//

iXG 100MP, iXG 100MP Wide Spectrum and iXG 100MP Achromatic
Phase One iXH/iXG
ce (RS) leaf shutter, integrated in lens n-Sensor Electronic shutter (ES)
1/250s - 1hr
Close range to near infinity, 21 mm max. extension
lotorized & encoded, controlled from Capture One CH software
andard Arca-Swiss dovetail and a 3/8" threaded hole with a dedicated L-Bracket
USB3.0
Flash Output, remote triggering
Integrated heat sink
Focused to infinity: 150 x 120 x 100 Focused to close range: 180 x 120 x 100
2300 (Including 72 mm lens and mounting bracket)
10-35 (office environment)
15-80 (office environment)

	Schneider Kreuznach	Schneider Kreuznach
	72mm RS-iXG	120mm RS-iXG
)	Infinity to 1:0.9 with extension tubes	1:6,9 to 1:1,2 with extension tubes

40.5

46.0

Phase One XF Camera System

Built on many years of experience in the high end photographic market, the Phase One XF Camera System brings unrivaled quality, accuracy, and reliability, and sets a new standard for a flexible platform equipped with everything that is needed for reproduction at the highest possible level.

• Robust, solid, aluminum-alloy construction.

PHASEONE

- Advanced, expandable operating system.
- Intuitive and easily customizable user interface.
- Choice of fully integrated Waist Level and Prism viewfinders.
- Support for all Schneider Kreuznach LS 645 format lenses, from 28 mm to 240 mm.
- Support for all Phase One and Mamiya Focal Plane lenses and many legacy Mamiya 645 lenses.
- Advanced HAP auto focus system with remote control from Capture One.
- Compatible with all Phase One IQ Digital Backs with a choice of 100-150 Megapixel.



ers. es, from 28mm to 240mm. s and many legacy Mamiya 645 lenses m Capture One. pice of 100-150 Megapixel

XF Camera System Highlights



Honeybee Autofocus Platform

HAP-1 is designed with a custom processor, coupled with a The waist-level finder is convenient for many styles of high-resolution CMOS AF sensor. Combining a unique floating- photography, be it in studio or on location. With the ability to point architecture and a fully programmable interface, HAP-1 attain a more effective working position, the waist-level finder allows for continuous tailoring and tuning of the AF system, is a great addition to the creative toolbox. providing user-accessible software updates for years to come. The new Hyperfocal Point Focusing, creates unique presets designed HAP-1 autofocus platform. Using this ability, light for each lens which make HAP-1 automatically return to that metering is now available with our waist-level finder. specific point on demand.

Sequence Photography

Focus stacking - Select the desired focus plane and the camera will create a series of images with multiple focusing steps and these can be then stacked in 3rd party software solutions to give a greater depth of field.

Intervalometer - The camera can be programmed to take a series of images at fixed intervals.

Exposure bracketing - When there is a need to record an extremely wide dynamic range, the camera can be programmed to create a series of images with fixed ISO and aperture but with variable exposure times.

New Modular Viewfinders

The XF Camera System can measure the light on the newly

With a solid glass prism, the 90° viewfinder is the brightest of its kind and has virtually no loss of light. Together with nearly 100% frame coverage, the prism viewfinder displays a perfect view of the scene and comes standard on all XF Camera Systems.

OneTouch User Interface

The OneTouch UI on the XF Camera System is a seamless combination of intuitive dials, keys and touch screen interactions. Each operation is used only where it makes sense and where you want it. OneTouch UI is designed with the goal of making controls so simple that photo-graphers will feel at home within moments of getting started. The 1.6" grip screen is designed for clear visibility in any lighting condition using a transflective capacitive.

XF Camera System

Technical Specifications

Imaging Sensor



Size & Weight

XF Camera w/ 90° pris

Battery

Battery	BP-911/914/915 3400 mAh
Powershare	IQ4/IQ3 only
Power Input	With accessory
Internal battery charging	XF and IQ4/IQ3
Support for USB 3 charging hub (1.5 A)	IQ3 only
Power over Ethernet	IQ4 only

Imaging Sensor

Digital Back options	IQ3 50-100MP & IQ4 100-150MP with XF mounts (See specification for Digital Backs)
Backwards compatibility	IQ1 & IQ2 with P mounts

	Dimensions	Weight
XF Camera System* w/ 90° prism viewfinder	152 x 135 x 160 mm	1390 g
XF Camera System* w/ waist level finder	152 x 173 x 160 mm	1020 g
XF Camera Body w/o battery	152 x 108 x 85 mm	790 g
IQ Digital Back	98,5 x 88,5 x 62,3 mm	695 g
90° prism viewfinder	67 x 17 x 57 mm (closed)	500 g
Waist level finder	67 x 17 x 57 mm (closed) 67 x 65 x 57 mm (open)	130 g
*without lens		

Flash

Flash trigger	Integrated Profoto wireless
Wireless trigger range	20m (outside)
Back flash sync	Yes
Flash sync speed focal plane shutters (max)	XF and IQ4/IQ3
Support for USB 3 charging hub (1.5 A)	1/125s
Flash sync speed leaf shutters (max)	1/1600s

IQ Digital Back Range

Technical Specifications



1.2

0.7







1.2

0.7

Specifications	IQ4	150MP	IQ4 1 Achro	50MP omatic	IQ4 10 Trichro	DOMP omatic		IQ3 100MP	
Resolution	151 Me	egapixel	151 Me	gapixel	101 Meg	gapixel		101 Meç	gapixel
Long exposure	60 n	ninutes	60 m	ninutes	60 mi	inutes		60 mi	nutes
16 bit Opticolor+	•	Yes	Y	⁄es	Ye	es		Yes	
Sensitivity (ISO)	50 -	25600	200 -	102400	35 - 1	2800		2800	
Sensor type	CI	MOS	CN	10S	CM	10S		CMOS	
Sensor size	53.4	1 x 40	53.4	53.4 x 40		x 40		53.4 >	x 40.1
Active pixels	14204	x 10652	14204 x 10652		11608 x 8708		11608 x 8708		
Pixel size (micron)	3.76 × 3.76		3.76 x 3.76		4.6 x 4.6			4.6 >	4.6
Output image dim. 300dpi	120.26 x 90.19 cm		120.26 x 90.19 cm		98.3 x 73.2 cm			98.3 x 7	73.2 cm
Output image dim. 600dpi	60.13 x	45.09 cm	60.13 x -	60.13 x 45.09 cm		36.9 cm		49.1 x 3	6.9 cm
Mount options*		XF)	KF	×	Έ		XF, H	
3.2" touch display	````	Yes Yes Yes		es		Yes			
High bandwith interface	Yes		Yes		Yes		Yes		
XF Powershare	```	Yes	Yes		Ye	es		Yes	
Wi-Fi 802.11	Yes		Yes		Yes			Yes	
Captures per second	14-bit	16-bit	14-bit	16-bit	14-bit	16-bit		14-bit	16-bit
Focal plane (full res.)	1.4	0.7	1.4	0.7	1.4	0.7		1.4	0.7

1.2

0.7

1.2

0.7

Leaf shutter (full res.)



IQ3 100MP Achromatic

101 Megapixel
60 minutes
Yes
200 - 51200
CMOS
53.4 x 40.1
11608 x 8708
4.6 × 4.6
98.3 x 73.2 cm
49.1 x 36.9 cm
XF
Yes
Yes
Yes
Yes

14-bit

16-bit

1.1	0.6
0.9	0.5

Phase One Lenses

Schneider Kreuznach Blue Ring Lenses



45mm LS f/3.5



55mm LS f/2.8



80mm LS f/2.8

Providing a focal length that is perfect for almost any application, the Blue Ring 45mm f/3.5 offers edge-toedge sharpness and nearly distortion free results.

- Tack sharp wide-angle lens
- Minimum optical distortion
- Flash synchronization up to 1/1600th

Minimal distortion semi-wide-angle design provides a normal look, great for editorial portraits and lifestyle photography.

- Fast aperture, shallow depth of field
- Compact size with LS capabilities

A preferred choice for location fashion photographers using fill flash and an essential lens for every photographers kit.

- Fast aperture allowing shallow depth of field
- Edge-to-edge sharpness
- Extreme optical performance





110mm LS f/2.8

120mm LS f/2.8

A longer focal length with just enough optical compression for full-length fashion, beauty and portraiture.

- Fast lens allowing shallow depth of field
- Extreme anti-flare optical design

Macro lens ideal for close-up product shots, and equally ideal for close up beauty, action, nature and wildlife photography.

- Edge-to-edge tack sharp images
- Beautiful out-of-focus bokeh
- Auto Focus and Manual focus

Our fastest telephoto lens, providing razor thin depth of field at f/2.8. Perfect for studio and location portraiture.

For the full range of available lenses please see www.phaseone.com





150mm LS f/2.8

• Fastest telephoto lens • Auto and manual focus • Razor thin depth of field

Phase One AutoColumn Copy Stands



LED insert



Phase One RPS 2300XL - Floorstand AutoColumn copy stand with LED option



The new standard of AutoColumn copy stands, the Phase One RPS 2300XL, is designed with motorized AutoColumn technology to accomodate for efficient work with theiXH 150MP andiXH 150MP and iXG 100MP 100MP camera system and Capture One CH.

The Phase One RPS 2300XL features high precision camera positioning, and a geared movable camera arm. A camera leveling head secures precise and quick positioning. A LED baseboard insert is available for transparency scanning.

Wall mount options are available for the 2300XL column as well as upgrades for existing RPS 2300 products in the field.

Specifications

Base plate	100 x 75 cm (39,4 x 29,5 in.)					
LED insert plate	42 x 32 cm, 6500K, dimmable					
Maximum load	10 kg (22 lbs)					
Camera mounting plate	Arca Swiss type quick release					

Phase One RPS 1600 - Tabletop AutoColumn copy stand with LED option



The new standard of AutoColumn copy stands, the Phase One RPS 1600, is designed with motorized AutoColumn technology to accomodate for efficient work with theiXH 150MP andiXH 150MP and iXG 100MP 100MP camera system and Capture One CH.

The Phase One RPS 1600 features high precision camera positioning, and a geared movable camera arm. A camera leveling head secures precise and quick positioning. An LED baseboard insert is available for transparency scanning.

100 x 70 cm (39.4 x 27,5 in.)	
1.60 m (6.2 ft.)	
42 x 32 cm, 6500K, dimmable	
10 kg (22 lbs)	
Arca Swiss type quick release	

Phase One 2-Motion Copy Stand



Phase One 2-Motion Maximum flexibility for larger objects

The RSP 2-Motion adds an adjustable, motorized 100 x 80 cm baseboard allowing for greater flexibility and use of different lenses when scanning larger objects. The baseboard can be fitted with a steel sheet plate up to DINAO format for magnetic attachment of large drawings, maps etc.

Specifications

Total height

PHASEONE

Maximum working spa

Column cross section

Maximum load

Base board

Camera platform

Connecting thread (interchangeable)

Required floor space (WxD)

	227 cm (89.4 in.)
in	160 cm (63 in.)
	120 x 80 mm (4.7 x 3.1 in.)
	on camera carrier: 10 kg (22 lbs) on base board: 15 kg (33 lbs)
	100 x 80 cm (39.4 x 31.5 in.)
	13 x 13 cm (5.1 x 5.1 in.)
	1/4" / 3/8"
e	100 x 126 cm (39.4 x 49.6 in.)

Cultural Heritage Solution Partners

Phase One

Phase One is the world leader in open-platform medium format digital camera systems and solutions designed to deliver the highest image quality for professional photography.

Our products are built by hand using the best materials, highest precision and most advanced quality assurance processes.

Our company was born digital and we have always strived to deliver the highest image quality possible through innovative solutions. Well known Cultural Heritage institutions worldwide rely on our combined systems to consistently deliver the highest level of quality, performance and safety for demanding collections of objects.

Phase One was founded in 1993 and is based in Copenhagen with offices in New York, London, Tokyo, Cologne, Hong Kong and Shanghai.

Phase One is proud to work together with the world's leading value added resellers. In doing so we ensure the highest level of service and support to our customers.

Digital Transitions, USA

The Digital Transitions' Division of Cultural Heritage provides cameras and copy-stand solutions to support the digitization programs of libraries, museums, archives, collectors, service bureaus and other institutions.

Digital Transitions' approach is comprehensive. They work closely with every client to design a complete solution

with an efficient standards-based workflow. This includes careful choice of hardware, integrating our systems into existing infra-structures, and providing ongoing support and training to staff in order to keep the digitization program running efficiently.

For more information, please visit: http://dtculturalheritage.com

Cambo, The Netherlands

Cambo BV, founded in 1946, is based in the town of Kampen in The Netherlands, and today works from a modern 2,000 sq.m. facility with the latest computer controlled design and machine tools, ensuring production to the highest standards. Cambo produces a range of camera support stands and

other studio accessories, including dedicated Reproduction cameras and Reproduction stands. For more information, please visit: http://www.cambo.com/en/

Kaiser Fototechnik, Germany

For more than 40 years, the copy stands from Kaiser Fototechnik have been chosen by photographers, libraries, and archives for professional repro-graphic work. Together with Phase One's camera solutions and software, we have created a line of Instant Capture solutions for efficient and high quality digitization projects. For more information, please visit: http://www.kaiser-fototechnik.de/en/





Phase One Scanning Solutions

CH Product Portfolio	Suitable Resolution (Size@PPI)	Baseboard size	Auto-column	2motion: Table and camera	Table-top	Floor-standing	Wall-mount	Column heigth	Light table for film scanning
Film scanning solutions (+/- Autocolumn solution)									LED insert
- Film scanning solution with Autocolumn, iXH 150MP and iXG 100MP	Down to 6 x 4.5 cm @5500ppi	100 x 70 cm	Yes		Yes		N/A	1.6 m	LED insert
- Film scanning solution with Autocolumn, without camera		100 x 70 cm			Yes		N/A	1.6 m	LED insert
- Film scanning solution, Kaiser rePro iXH 150MP and iXG 100MP	Down to 6 x 4.5 cm @5500ppi	80 x 60 cm	No		No	Yes	N/A	1.5 m	Kaiser Light Box
- Film scanning solution, Kaiser rePro, without camera		80 x 60 cm	No		No	Yes	N/A	1.5 m	Kaiser Light Box
									,
Flat copy scanning solutions (with AutoColumn or 2-motion solution)									
- General purpose scanning solution with Autocolumn, iXH 150MP and iXG 100MP	Up to A1+ @400ppi	100 x 75 cm	Yes		No	Yes	N/A	2.3 m	LED insert
- Optional LED insert for baseboard		42 x 32 cm			Yes		N/A		LED insert
- Wall mounted General purpose scanning solution with Autocolumn, iXH 150MP and iXG 100MP	Up to A0+ @300ppi	N/A	Yes		No		Yes	2.3 m	
- Upgrade scanning solution with Autocolumn for existing Cambo RPS, iXH 150MP and iXG 100MP	Up to A1+ @400ppi	100 x 75 cm	Yes		N/A	Yes		2.3 m	
- Upgrade kit with Autocolumn for existing Cambo RPS, iXH 150MP and iXG 100MP	Up to A2 @350ppi	100 x 75 cm	Yes		N/A	Yes		2.3 m	
- General purpose scanning solution with 2-motion, iXH 150MP and iXG 100MP	Up to A1+ @400ppi	100 x 80 cm	No	Yes	No	Yes	N/A	1.6 m	Kaiser Light Box
Book scanning solutions (single- or dual camera solution)									
- Book scanning solution, DT Atom flexible book cradle, with Autocolumn, iXH 150MP and iXG 100MP	Bound: A3 @1000ppi Open 180° A2 @600ppi	59 x 65 cm	Yes		Yes		N/A	1.4 m	DT Photon LED
- Book scanning solution, DT Versa 180 degrees cradle, with Autocolumn, iXH 150MP and iXG 100MP	Bound: A2 @400ppi Open 180° A1 @400ppi	102 x 76 cm	Yes		N/A	Yes	N/A	1.6 m	Kaiser Light Box
- Book scanning solution, BC100 dual camera, 100 degrees cradle, iXH 150MP and iXG 100MP	Up to A2 @500ppi	A2	No		N/A	Yes	N/A		DT Photon LED



References

Partial list

USA

American Museum of Natural History New York, NY

Smithsonian Institution Washington DC, PA

Library of Congress Washington DC, PA

Harvard University Cambridge, MA

Museum of Modern Art New York, NY

New York Public Library New York, NY Walt Disney Studios Burbank Glendale, CA

Standford University Standford, CAA

The U.S. National Archives Washington, DC

UK The British Museum London

The British Library London

The Bodleain Library Oxford The John Rylands Library Manchester

Cambridge University Library Cambridge

The Netherlands The National Maritime Museum Amsterdam

Picturae Heiloo

France The National Library of France Paris